




S-2YCY 8 x 0.23/1.50

Coaxial SDH-Switch Board Cables acc. to Finnish specification



Application


Standards

acc. to Finnish specification

Flame resistance

Construction

Inner conductor	copperclad steel wire, bare, diameter 0.23 mm ± 0.005 mm
Insulation	PE 1.50 mm ± 0.05 mm
Outer conductor	copper braid, bare
Sheath	PVC 2.5 mm ± 0.10 mm grey
Cable lay up	8 coaxials twisted to the bundle with number printing 1-8
Wrapping	PET-foil
Sheath	PVC 11.4 mm ± 0.5 mm grey RAL 7001



S-2YCY 8 x 0.23/1.50

Electrical properties

at 20°C

DC resistance	Inner conductor	≤ 1000 Ω/km
Mutual capacitance		67 nF/km
Characteristic impedance		75 Ω ± 3.0 Ω
Velocity ratio		66 %
Transfer impedance	1 MHz – 30 MHz	≤ 60.0 mΩ/m
Max. operating voltage		0.750 kV
Test voltage	Inner/Outer conductor	1.5 kV _{DC} 1 min
Insulation resistance		≥ 10 GΩ*km

Electrical data

at 20°C

Attenuation (dB/100m)		Crosstalk (dB/100m)		Return loss (dB)	
Frequency (MHz)		Frequency (MHz)		Frequency (MHz)	
1	≤ 2.9	0.3 – 1	≥ 60	1-100	≥ 20
2	≤ 4.1	1.0 – 30	≥ 60		
4	≤ 5.8				
10	≤ 9.0				
17	≤ 11.6				
50	≤ 17.5				
70	≤ 20.4				
100	≤ 24.5				
140	≤ 29.0				
200	≤ 35.0				
1000	≤ 76.0				

Technical data

Product code	Designation	Type	Outer diameter mm	Weight kg/km	Standard delivery length m	Drum size KTG/ring	Gross weight kg	Copper content	Tensile force N
CS2720901	S-2YCY	8 x 0.23/1.50	11.4	155	500 ± 20	071	103	45	225